



BATTERIE PER "NAUTICA" E "CAMPER"

www.infrarossi.it



BATTERIE PIOMBO ACIDO

MODELLO	TENSIONE NOMINALE V	SPUNTO CCA 0°F	SPUNTO CA 32°F	CAPACITÀ 5 ore (AH)	CAPACITÀ 20 ore (AH)	DIMENSIONI (mm)			PESO Kg.
						LARGHEZZA	PROFONDITÀ	ALTEZZA	
24TMS	12	470	575	62	72	286	171	248	19
27TMS	12	550	675	73	85	324	171	248	21
C31-850A	12	750	920	-	-	330	173	238	24
C31-850S	12	750	920	-	-	330	173	238	24
C31-1000A	12	1.000	1.225	-	-	330	173	238	28
C31-1000S	12	1.000	1.225	-	-	330	173	238	28
4D-2	12	1.000	1.220	-	-	524	221	241	45
8DX-2	12	1.200	1.470	-	-	521	278	241	54



BATTERIE SIGILLATE "AGM"

MODELLO	TENSIONE NOMINALE V	SPUNTO CCA 0°F	SPUNTO CA 32°F	CAPACITÀ 5 ore (AH)	CAPACITÀ 20 ore (AH)	DIMENSIONI (mm)			PESO Kg.
						LARGHEZZA	PROFONDITÀ	ALTEZZA	
24-AGM	12	440	620	61	80	275	168	208	24
27-AGM	12	560	780	76	99	305	168	208	30
31-AGM	12	720	950	83	110	332	175	213	32
4D-AGM	12	1.110	1.420	131	165	530	210	214	52
8D-AGM	12	1.450	1.850	179	230	521	268	203	70



BATTERIE SIGILLATE "AGM"

MODELLO	TENSIONE NOMINALE V	AVVIAMENTO A (5 sec) / 25°C	CAPACITÀ 5 ore (AH)	CAPACITÀ 20 ore (AH)	DIMENSIONI (mm)			PESO Kg.
					LARGHEZZA	PROFONDITÀ	ALTEZZA	
ZGL12-60	12	900	51	60	229	138	212	18,3
ZGL12-70B	12	1.050	59	70	260	169	215	25
ZGL12-80B	12	1.200	68	80	351	167	179	24,8
ZGL12-80A	12	1.200	68	80	260	169	215	28,5
ZGL12-100B	12	1.500	85	100	328	172	220	34,2
ZGL12-120B	12	1.800	102	120	331	175	239	35
ZGL12-160A	12	2.400	136	160	484	171	241	49,6
ZGL12-200	12	3.000	170	200	530	209	218	65,5
ZGL12-230	12	3.450	195	230	522	242	222	76,5
ZGL12-240	12	3.600	204	240	520	269	208	78
ZGL12-260	12	3.900	221	260	521	269	224	89

